


QDM Quick Disconnect Sling Swivel



- WARNING: BEFORE STARTING, MAKE SURE THE WEAPON IS UNLOADED, The Chamber is empty, and the safety engaged.
- A CAUTION: PLEASE READ ALL INSTRUCTIONS BEFORE PROCEEDING. COMPONENTS UNDER SPRING PRESSURE MAY EJECT FORCEFULLY AND COULD CAUSE INJURY.
- ▲ WARNING: OBSERVE SAFE FIREARM HANDLING PRACTICES AT ALL TIMES.


 FAILURE TO DO SO MAY RESULT IN SERIOUS BODILY INJURY OR DEATH.

 MAGPUL INDUSTRIES SHALL NOT BE RESPONSIBLE FOR INJURY, DEATH OR


 PROPERTY DAMAGE RESULTING FROM FAULTY INSTALLATION, MISUSE,

 ILLEGAL USE, OR MODIFICATION OF THIS PRODUCT.

INSTALLATION INSTRUCTIONS



To connect the *QDM Sling Swivel* to the sling, run the end of the *MS1 Sling* through the *QDM Sling Swivel* and then back through the *Fit Buckle(s)*. Double the webbing back through the upper *Fit Buckle* if possible.



Grip actuation surfaces with finger/thumb and push into socket.

